

Specifications

Range	Conductivity	0 to 100, 100 to 1000 uS; 1 to 10, 10 to 100, 100 to 200 mS (autoranging)
	TDS	0 to 100, 100 to 1000 ppm; 1 to 10, 10 to 100, 100 to 200 ppt (autoranging)
	Resistivity	10 K Ω to 30 M Ω
	Temperature	32 to 160°F (0 to 71°C)
Resolution	Conductivity	0.01, 0.1 uS; 0.01, 0.1, 1.0 mS
	TDS	0.01, 0.1 ppm; 0.01, 0.1, 1.0 ppt
	Resistivity	0.01 (<100 K Ω); 0.1 (<1000 K Ω); 0.1 (>1 M Ω)
	Temperature	0.1
Accuracy	Conductivity	±1% of reading
	TDS	±1% of reading
	Resistivity	±1% of reading
	Temperature	±0.2°F(±0.1°C)
Temp compensation		Automatic for 0 to 71 °C
Min Sample Size		Conductivity = 5 mL
Output		IR download with optional uDock accessory
Conductivity temp coefficient		0 to 9.99%/°C
Body Type		Valox, IP 67 rated
Power		One 9V battery (included)
Battery life		>100 hours
Dimensions		2-3/4" W x 2-1/2" H x 7-3/4"D
Memory		100 measurements with time and date stamp
Model		4PII